



CORDE 4 SEATING FABRIC COLORS

FABRIC FOR THE **CHESAPEAKE** AND **WORLD** CHAIRS.

Scroll down below to view our fabric swatches.

MCE offers the Corde 4 upholstery seating line. Corde 4 is a woven four-way stretch fabric specially designed for ergonomic seating applications. It features a small modular weave of high-performance nylon and polyurethane, making it durable and long lasting, as well as comfortable and visually appealing.



Note: The fabrics featured are provided as a general guide and do not guarantee exact duplication of colors, textures or designs. To ensure the fabric selection meets your expectations, please request a sample from your Account Representative.



CORDE 4 COLORS

Chesapeake and World Chairs



Black - CF10

BLACK-CF10

Contents: 96% nylon, 4% Polyurethane

Width: 51"

Seat: 1/8' horizontal, 1/4" vertical


Abrasion: 150,000 double rubs, ASTM 4157, #10 cotton duck, Wyzenbeek

Brush Pill: Class 5, ASTM D 3511

Flammability: Passes California Technical Bulletin 117, Section E

Colorfastness to light: Class 4.5, 40 hours at AATCC, Test Method 16E

Crocking: Dry: Class Grade 4.5, Wet: Class 4.5, AATCC Method 8



Medium Grey - CF56

MEDIUM GREY-CF56

Contents: 96% nylon, 4% Polyurethane

Width: 49.5"

Seat: 1/8' horizontal, 1/4" vertical


Abrasion: 150,000 double rubs, ASTM 4157, #10 cotton duck, Wyzenbeek

Brush Pill: Class 5, ASTM D 3511

Flammability: Passes California Technical Bulletin 117, Section E

Colorfastness to light: Grade 4.5, 40 hours at AATCC, Test Method 16E

Crocking: Dry: Grade 5, Wet: Grade 5, AATCC Method 8



Parma Red - CF78

PARMA RED-CF78

Contents: 96% nylon, 4% Polyurethane

Width: 51"

Repeat: 1/8' horizontal, 1/4" vertical

Abrasion: 150,000 double rubs, ASTM D 4157/ACT 150K, #10 cotton duck, Wyzenbeek

Brush Pill: Class 5, ASTM D 3511

Flammability: Passes California Technical Bulletin 117-2013

Colorfastness to light: Grade 4.5, 40 hours at AATCC Test Method 16E

Crocking: Dry: Class 4.5, Wet: Class 4.5, AATCC Test Method 8



Thalo - CF52

THALO-CF52

Contents: 96% nylon, 4% Polyurethane

Width: 51"

Repeat: 1/8' horizontal, 1/4" vertical

Abrasion: 150,000 double rubs, ASTM D 4157/ACT 150K, #10 cotton duck, Wyzenbeek

Brush Pill: Class 5, ASTM D 3511

Flammability: Passes California Technical Bulletin 117-2013

Colorfastness to light: Grade 4.5, 40 hours at AATCC Test Method 16E

Crocking: Dry: Class 4.5, Wet: Class 4.5, AATCC Test Method 8